DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D212-664 Rev. G OR LATER
AND INSTRUCTIONS FOR CONTINUOUS AIRWORTHINESS ICA-D212-664 Rev. 8 OR LATER
REF. CANADIAN STC: SH01-9
REF. FAA STC: SR01298NY
REF. EASA STC: EASA.IM.R.S.01304

FOR D212-664-107 & D212-664-107B CROSSTUBES AT CHG 003, A HEAVIER WALL EXTRUSION WAS USED TO MANUFACTURE THE PARTS BECAUSE OF PROCUREMENT ISSUES WITH THE STANDARD MATERIAL. THE REVISED WEIGHT AND BALANCE IS GIVEN BELOW:

Aircraft	DART CROSSTUBE P/N	DESCRIPTION	WEIGHT	STA	MOMENT
205, 210,	D212-664-107	Standard Fwd	28.7 lb	71.5 in	2052 in lb
212, 214, UH-1H	D212-664-107B @ CHG 003		(13.0 kg)	(1.82 m)	(23.7 m kg)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-0-01

BY: D. SHEPHERD (DE # 02)

DATE: 11.10.26
CERT. NO.: SH01-9
ISSUE NO.: 3

Α	NEW ISSUE			СР	11,10.26	
REV.		DESCRIPTION			DATE	
DESIGN	·	P	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA			
DRAWN		P				
CHECK	ĒD	AS5	DRAWING NO.		REV. A	
MFG. AF	PPR.	N/A	DSI 9582	S	HEET 1 OF 1	
APPRO	√ED	4	TITLE		SCALE	
DE APP	R.	#	CROSSTUBE WEIGHT DEVIATION NTS			
DATE 11.10.26			COPYRIGHT © 2011 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT			